



HEALTHCARE



## PROFESSIONAL MOUNTING SOLUTIONS

Chief monitor mounts create healthcare workstations that meet the needs of today's healthcare professionals. Perfect for most health-related applications, Chief mounts move with the user providing the most stable, simple-to-use, space-conscious workstations available.

[www.chiefmfg.com](http://www.chiefmfg.com)




# PROFESSIONAL MOUNTING SOLUTIONS

## FLAT PANEL & MONITOR MOUNTS

# MOBILE WORKSTATIONS RADIOLOGY LABS NURSES STATIONS PATIENT ROOMS

### SINGLE MONITOR MOUNTS



### MULTI-MONITOR MOUNTS



## WHY CHIEF?

1

### EFFORTLESS HEIGHT ADJUSTMENT

Smooth, fluid height adjustment accommodates the vast majority of users. Once adjusted, the screen stays put without the use of levers or knobs.

2

### CENTRIS™ TECHNOLOGY

This patented feature provides gravity-centered fingertip adjustment for easy tilt and side-to-side pivot. Simple grasp, move and release monitor. Screens in multi-monitor solutions are independently adjustable for proper ergonomic alignment

3

### SPACE-SAVING DESIGNS

Chief's full swing mounts collapse to an ultra-low profile, maximizing workspace utilization.

4

### EASY INSTALLATION

No assembly required. Convenient keyhole eyelets for monitor install with universal VESA® compliant interface.

3

*Preferred mount for PACS applications*



More information on Chief products, visit us on the web at [www.chiefmfg.com](http://www.chiefmfg.com).

# MONITOR SOLUTIONS

## APPLICATIONS

Ideal for:

- Radiology Suites
- PACS (Picture Archiving and Communications Systems)
- EHR (Electronic Health Records)



KCG110



KCY220

## SPECIFICATIONS

Model	Screen Size Range	Extension Range	Tilt	Weight Capacity
<b>Monitor Solutions</b>				
KCG110	10 - 30"	2.19 - 20" (56 - 508 mm)	±15°	5 - 25 lbs (2.3 - 11.4 kg)
KCY220	10 - 26"	2.19 - 20" (56 - 508 mm)	±15°	5 - 20 lbs (2.3 - 9.1 kg) per arm

Model	Number of Monitors	Max Monitor Width	Max Monitor Height	Pole Height	Tilt	Weight Capacity (per monitor)
<b>Table Stand Arrays</b>						
KTP220	2	22.7" (577 mm)	26" (660 mm)	14" (356 mm)	±15°	35 lbs (15.9 kg)
KTP225	2	30" (762 mm)	26" (660 mm)	14" (356 mm)	±15°	35 lbs (15.9 kg)
KTP230	2	-	19.3" (490 mm)	29.75" (756 mm)	±15°	35 lbs (15.9 kg)
KTP320	3	18" (457 mm)	26" (490 mm)	14" (356)	±15°	30 lbs (13.6 kg)
KTP440	4	22.7" (577 mm)	18" (457 mm)	28.5" (724 mm)	±15°	20 lbs (9.1 kg)
KTP445	4	30" (762 mm)	18" (457 mm)	28.5" (724 mm)	±15°	20 lbs (9.1 kg)



KTP220



KTP225



KTP320



KTP230



KTP440



KTP445

# HEALTHCARE SOLUTIONS

## FLAT PANEL TV SOLUTIONS

### APPLICATIONS

Ideal for:

- In-Patient Rooms
- Conference Rooms
- Lobbies
- Operating Rooms

### ACCESSORIES

**Steel Stud Drywall Anchor Kits:**  
For Fixed & Tilt Wall Mounts


- PAC115
- PAC116
- PAC117




FWDSK



JWDSK




MWRSK



PWRSK



FSRV



MSRV/U



PLPU



FTRV



MTRV/U



PSTU

### SPECIFICATIONS

Model	Screen Size Range	Depth/Extension from Wall	Tilt	Weight Capacity
<b>Steel Stud Solutions</b>				
FWDSK	10 - 26"	2.85 - 15.85" (72 - 403 mm)	±15°	25 lbs (11.3 kg)
JWDSK	27 - 45"	3.5 - 20.38" (89 - 517 mm)	±15°	75 lbs (34 kg)
MWRSK	30 - 50"	3.38 - 24.88" (89 - 632 mm)	+5/-15°	100 lbs (45.4 kg)
PWRSK	42 - 65"	3.5 - 25" (89 - 635 mm)	+5/-15°	100 lbs (45.4 kg)

### Fixed Flat Panel Solutions

FSRV	10 - 26"	.75" (19 mm)	-	45 lbs (20.4 kg) stud 30 lbs (13.6 kg) drywall
MSRV	27 - 45"	1.56" (40 mm)	-	100 lbs (45.4 kg)
MSRU	30 - 50"	2.25" (57 mm)	-	125 lbs (56.7 kg)
PSTU	42 - 65"	2.31" (59 mm)	-	200 lbs (90.7 kg)

### Tilt Flat Panel Solutions

FTRV	10 - 26"	1.94" (50 mm)	+5/-15°	45 lbs (20.4 kg) stud 30 lbs (13.6 kg) drywall
MTRV	27 - 45"	1.81" (46 mm)	-15°	100 lbs (45.4 kg)
MTRU	30 - 50"	2.5" (64 mm)	-15°	125 lbs (56.7 kg)
PLPU	42 - 65"	2.31" (59 mm)	-15°	200 lbs (90.7 kg)

Products ending in V ship with a VESA® interface. Products ending in U ship with a universal interface bracket.

MSR, PST, MTR and PLP are pre-approved OSHPD products.



# PROFESSIONAL MOUNTING SOLUTIONS

## MONITOR MOUNTS

### WORKSTATION SOLUTIONS

#### APPLICATIONS

Ideal for:

- Patient Bedside Charting



*KWGSK Steel Stuf Monitor Mount and  
KSA1021 Keyboard Tray Accessory  
(sold separately)*



*KWT110  
(Includes slat wall extrusion, KSA1020 CPU mount,  
KWG110 Dual Arm Mount, KWK110 Keyboard Mount)*



*KWT110 extended*

*KWT110 collapsed*

#### SPECIFICATIONS

Model	Depth	Max Extension	Height Adjustment	Tilt	Weight Capacity
<b>KWT110 Wall Track Solution</b>					
KWG110	2.19" (56 mm)	19.5" (495 mm)	13.25" (337 mm)	±15°	5 - 25 lbs (2.3 - 11.4 kg)
KWK110	3.33" (85 mm)*	29.2" (742 mm)	13.25" (337 mm)	5° & 90°	10 lbs (4.5 kg)
KSA1020	0 - 7.5" (0 - 191 mm)	–	9.75 - 18" (248 - 457 mm)	–	40 lbs (18.1 kg)
<b>Other Configurations</b>					
KWGSK	2.85" (72 mm)	19.37" (492 mm)	13.25" (337 mm)	±15°	25 lbs (11.3 kg)
KSA1021	8" (203 mm)**	–	2" (51 mm)	–	Reduces capacity of mount by 5 lbs (2.3 kg)

\*When keyboard is stored in flipped up position. \*\*Maximum keyboard depth.



# PROFESSIONAL MOUNTING SOLUTIONS

## FLAT PANEL MOUNTS

### MOBILE CARTS & STANDS

#### APPLICATIONS

Ideal for:

- Video Conferencing



PFC



PF1

#### SPECIFICATIONS

Model	Screen Size Range	Height Adjustment	Tilt	Weight Capacity
<b>Flat Panel Carts</b>				
MFC	30 - 55"	4 - 6' (120 - 180 cm)	±15°	125 lbs (56.7 kg)
PFC	42 - 71"	4 - 6' (120 - 180 cm)	±15°	200 lbs (90.7 kg)
<b>Flat Panel Stands</b>				
MF1	30 - 55"	4 - 7' (120 - 210 cm)	±15°	125 lbs (56.7 kg)
PF1	42 - 71"	4 - 7' (120 - 210 cm)	±15°	200 lbs (90.7 kg)



#### SERVICE EXCELLENCE

Chief products are backed by the best in customer service. Contact any of our Customer Service team members M-F, 7am to 7pm (CST) for assistance.



end-user focused      faster installation      superior service      proven quality

CHIEF MANUFACTURING ■ A DIVISION OF MILESTONE AV TECHNOLOGIES ■ [www.chiefmfg.com](http://www.chiefmfg.com)  
 USA/International ■ P 800.582.6480/952.894.6280 ■ F 877.894.6918/952.894.6918 ■ [chief@chiefmfg.com](mailto:chief@chiefmfg.com)  
 Chief Mounts Canada ■ p 877.345.4329 ■ F 888.377.5314 ■ [info@chiefmounts.ca](mailto:info@chiefmounts.ca)  
 Milestone Europe B.V. ■ p 31 (0)40 2668620 ■ F 31 (0)40 2668615 ■ [europe@milestone.com](mailto:europe@milestone.com)  
 Milestone AV Technologies Ltd ■ P 852.2145.4099 ■ F 852.2145.4477 ■ [asia.chief@milestone.com](mailto:asia.chief@milestone.com)

©2008 Milestone AV Technologies, a Duchossois Group Company. 800208B 10/08. Chief is a registered trademark of Milestone. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.